

Supply of Calibration Gas bottles

المواصفات :

No.	Description	Needed QTY	Qty at site
1	(CO) Gas Bottle 10 L; 500ppm, 150 Bar	1	2
2	(NO) Gas Bottle;10 L; 500ppm, 150 Bar	1	2
3	(SO2) Gas Bottle;10 L; 500ppm, 150 Bar	1	2
4	(NO2) Gas Bottle;10 L; 500ppm, 150 Bar	1	2
5	(CO2) Gas Bottle;10 L; 500ppm, 150 Bar	1	2
6	Calibration Gas in B10 AL Cylinder with CGA330 outlet valve: Volume : 1.382 Nm3 Pressure: 150 Bar	1	2
7	Calibration Gas in B10 AL Cylinder with BS4 outlet valve: Volume : 1.409 Nm3 Pressure: 150 Bar	NO 800 ppm m	(Tol : 5.0% Acc : 2.0%)
		SO2 800 ppm m	(Tol : 5.0% Acc : 0.5%)
		N2 99.84% m	(Tol : 2.0% Acc : 0.1%)
		CO 800 ppm m	(Tol : 5.0% Acc : 0.5%)
8	hazard gas calibration bottles Cylinder volume : 10 Ltr ST Valve type : BS-4 Fill pressure : 140 Bar	O2 20.9% m	(Tol : 2.0% Acc : 0.5%)
		N2 79.02% m	(Tol : 2.0% Acc : 0.5%)
		CH4 2.5%	(Tol : 5% Acc : 2%)
9	CO Gas Bottle Concentration:160ppm; volume:10L; Pressure:140Bar	O2 20.9% m	(Tol : 5% Acc : 2%)
		N2 BALANCE	(Tol : 5% Acc : 2%)
10	NO Gas Bottle Concentration:240ppm, volume:10L, Pressure:140Bar	1	1
11	CO2 Gas Bottle Concentration:20%, volume:10L, Pressure:140Bar	1	1
12	O2 Gas Bottle Concentration:20%, volume:10L, Pressure:140Bar	1	1

