

Description	Quantity	UOM
ACB, PN: Masterpact NW25H1, 2500A, 4 Poles, Icu= 65KA, Uimp= 12 KV, Withdrawable CB, With micrologic 6.0E LSIG Trip Unit, Includes (UC1, UC2, UC3, MCH, XF, MN, SDE1, OF1, OF2, OF3, OF4),	1	Each
ACB, PN: M-Pact MPA31W10, 1000A, 3 Poles, Icu= 50KA, Withdrawable CB, With Digital Trip Unit, Includes (Shunt Release ST, Closing Release CC, Spring Charging Motor),	1	Each
ACB, PN: Masterpact NT10H1, 1000A, 3 Poles, Icu= 42KA, Uimp= 12 KV, Withdrawable CB, With micrologic 6.0E LSIG Trip Unit, Includes (UC1, UC2, UC3, MCH, XF, MN, SDE1, OF1, OF2, OF3, OF4), SCHNEIDER ELECTRIC	1	Each
Automatic Transfer Switch Controller, PN: ATyS C30, With RJ45 terminal,	2	Each
Remote Control Interface, PN: ATyS D20, With RJ45 terminal,	2	Each
Multi-function Timer, PN: RE17RMMU, 1 C/O, T= (0.1s - 100h), Supply Voltage = (24 - 240 VAC) / (24 VDC), Nominal Output = 8A/250V,	2	Each
Under/Over Voltage Relay, PN: RM35TF30, Uc = (220-480V), Measurement Range = (220 - 480V), Nominal Output = 5A / 250V,	2	Each
Power Supply, PN: M-PRO APU PLC, Input: (175 - 275 VDC, 175 - 275 VAC 50Hz), Output: (22 - 26 VDC), Output Power ? 9.6 W,	2	Each
High-Capacity Dual Position Relay, PN: DCS-11, 220 VDC, Shanghai Relay Co.	2	Each
Relay, PN: JZX54P, 220 VDC, 14 Pins,	2	Each
Engine Generator Controller, PN: DSE 7310 MKII 7310-010-03, DC Supply: 8-35 V 0.5 A Max, DC Outputs: 24 V / 15 A (4-5) 2 A (8-13), DC Inputs: 30 V , Comms Port: 5 V Max,	1	Each
Automatic Battery Charger, PN: SNTL150P, Input Voltage = (95 - 265) VAC, Input Frequency = (47 - 63) Hz, Max. Input Current = 3 A, DC Output = 24 VDC / 5 A, Float Voltage = 27.6 VDC, Boost Voltage = 31.2 VDC,	1	Each
Definite Purpose Contactor, PN: 45FG20AG, 2 Poles, Full Load Current (FLA) = 35 A, Coil: (190 - 220 VAC) / 50 Hz) or (208 - 240 VAC) / 60 Hz, Open Enclosure,	2	Each
Battery Charger, PN: D-292265, AC input 120/240VAC, 50/60Hz, 1 Phase, 5.1/3A, DC output 26VDC, 10A, Allowable range of battery capacities : 50-200 AH ;	1	Each